

EM-KS4CEU-B

Electric scooter

Electric scooter with built-in display and application control.



HIGHLIGHTS

- 350W Motor
- Certified battery 36V 10 Ah
- Range per charge: 40 km
- Maximum speed 20 km/h
- 10" Pneumatic tyre
- Triple brake system
- Rear Suspension
- Turning indicator

Even better appearance and control of driving parameters, thanks to a new practical display. More safety will be ensured by turn signals in the steering bar and an additional drum brake on the front wheel.

e-scooter Features

Display	LED
APP Control	Yes
Bell	Yes
Tyre Pressure (PSI)	36
Tyres	Pneumatic
USB Port	Yes
Wheel Size (inches)	10
Braking	Disc brake / Drum brake / Power off brake
Charger Input (VAC/A)	100-240/1.8
Charger Output (VDC/A)	42/1.5
Driving Mechanism	Rear Wheel Brushless Motor (350W)
Foldable	Yes
IP Rating	IPX4
Maximum Incline (degrees)	15
Maximum Load (kg)	120
Maximum Speed (km/h)	20
Motor Power (Watts)	350
Range per Full Charge (km)	40
Start Mode	Kick Start
Suspension	Rear
Turn Indicator	Yes
Brake - Electronic	Yes
Brake - Front Wheel	Drum
Brake - Rear Wheel	Disc
Display Type	Alien
Turn Indicator - Handle Bar	Yes
Turn Indicators	Yes
Type of Headlight	Alien Head

Power Information

Power Requirements	100-240VAC 50/60HZ 1.8A
Power Consumption (W)	6.4
Standby Power Consumption (W)	0
Off Mode Power Consumption (W)	0
Safety Logo Certification	PLEV, RED, LVD, EMC, REACH, RoHS
Plug	CE Plug
Auto Power Off	Yes
External AC Adapter	Yes

Logistic Information

Box Size (W x H x D in mm)	205 x 535 x 1215
Gross Weight (kg)	22.7
Units on EU Pallet 1.8m	TBA
Container Load 40HQ	510
Container Load 40	445
Container Load 20	208
Units on UK CHEP Pallet 1.8m	TBA
Dimensions Folded (W x H x L in mm)	560 x 500 x 1180
Dimensions Unfolded (W x H x L in mm)	560 x 1230 x 1180
Foot Plate Size (W x L in mm)	160 x 483
Foot Plate to Top of Handlebars (mm)	1025
Ground to Foot Plate (mm)	180
EAN	5903802467772