

VELIS PRO



DOUBLE TANK
TECHNOLOGY



MULTIPOSITION



FLAT



ECO EVO
FUNCTION



ELECTRONIC
CONTROL



Electric water heater, multi-position installation,
ECO EVO function, flat model with a double tank,
magnesium anode and armored resistance

- / Shower ready + Hot water lamp
- / Power: 1,5/1,5 kW
- / Large and intuitive LCD front display
- / More hot water available thanks to the Double Tank Technology
- / Magnesium anode
- / Flat design with only 27 cm depth
- / Multiposition: installation both vertically and horizontal
- / Safety valve tested at 8 bar

ENERGY CLASS



TECHNICAL DATA		VELIS PRO 50	VELIS PRO 80	VELIS PRO 100
Installation		V/H	V/H	V/H
Nominal capacity	l	50	80	100
Heating element		Incoloy enameled x2	Incoloy enameled x2	Incoloy enameled x2
Anode		magnesium x2	magnesium x2	magnesium x2
Power	W	1.500/1.500	1.500/1.500	1.500/1.500
Voltage	V	220-240	220-240	220-240
Shower ready ($\Delta T=45^{\circ}\text{C}$)	h:min	0:46	0:46	0:46
Heating time ($\Delta T=45^{\circ}\text{C}$)	h:min	1:34	2:16	2:47
Maximum working temperature	$^{\circ}\text{C}$	80	80	80
Maximum working pressure	bar	8	8	8
Neto weight	kg	23,5	31	35,5
Class of protection	IP	X4	X4	X4
DIMENSIONS				
a	mm	781	1071	1256
b	mm	403	693	878
		VELIS PRO 50	VELIS PRO 80	VELIS PRO 100
Energy class Capacity profile		B	B	B
		M	M	M
CODE		3626135	3626136	3626137

REMARK:

The nominal capacity specified in this catalog indicates the product category.
The actual capacity of the product is specified in the relative technical documentation.

LEGEND

E Cold water inlet G 1/2"

S Hot water outlet G 1/2"

