

Lydos Wi-Fi

Wi-Fi
INTERFERENCEWATER PLUS
TECHNOLOGYECO EVO
FUNCTIONABSOLUTE
SAFETY
SYSTEMSHOWER
READYSECURITY
PROTECTIONTITANIUM
TECHNOLOGYITALIAN
DESIGN

/ WaterPlus Technology*: up to 16%*** more hot water

/ ECO EVO function powered by CoreTECH technology: energy savings up to 14 %

/ Ariston NET App: control and programming done remotely, via smartphone

/ Up to 25%*** energy savings thanks to Ariston NET app

/ Sending messages about potential problems in real time

/ Weekly programming of functions: up to 2 daily heating cycles

/ «Shower ready» function: number of available showers shown in the app

/ Remaining heating time function: time required to reach the set temperature displayed in the app

ENERGY CLASS



Ariston NET




TECHNICAL DATA

		50	80	100
Installation		V	V	V
Nominal capacity	l	50	80	100
Max. working pressure	bar	8	8	8
Power	kW	1.8	1.8	1.8
Voltage	V	230	230	230
IP protection	IP	IPX3	IPX3	IPX3
Max. working temperature	°C	80	80	80
Heat losses at 65 °C	kWh/24h	0.39	1.35	1.56
Heating time (37/49°C)	l/min	1.27	2.11	2.46
Weight	kg	16	20.5	24

DIMENSIONS

A	mm	528	733	885
---	----	-----	-----	-----



LEGEND

- Cold water inlet G 1/2"
 Hot water outlet G 1/2"

LYDOS Wi-Fi

	50	80	100
Energy class: ***	B	B	B
Profile capacity	M	M	M
CODE	32 003 74	32 003 75	32 003 76

NOTE:

The nominal capacity in this catalog indicates the product category. The actual product capacity is stated in the relative technical documentation.

* Patent in Spain, patent pending in the following countries: IL, FR, TR, RU, CN, VN, UAE.

** Maximum estimated savings, depending on the model. Comparison made using V40 results at maximum operating temperature between existing ARS products and new ARS products featuring WaterPlus technology.

*** Estimated savings of up to 25% on a daily basis, compared to a standard Ariston mechanical product.

*** In the range A + F.